

The UM-211 automated office blood pressure monitor provides your office with a consistent, highly accurate and reliable blood pressure measurement tool. Its features and durability are designed to meet the needs of in-clinic or office settings.

- Dual measurement mode (Auscultatory and Oscillometric)
- Cuff holder and grip for carrying
- Durable and chemical resistant body
- Professional cuff and 5 cuff sizes are available for use
- Large LCD display with backlight
- Rechargeable battery (300 measurements at full charged)
- Adjustable inflation pressure (AUTO/220/250/280)
- Irregular heartbeat (IHB) indicator
- Room temperature display







Stand-by display (Room temperature)

Measurement display

Easy to carry

Mercury-Free

Professional Blood Pressure Monitors



Auscultatory mode

UM-Series' auscultatory mode is designed for daily and frequent use. Selectable deflation speed (2.5 mmHg / sec. or 5.0 mmHg / sec.) and quick start for auscultatory mode are features `Only from A&D'.

- Quick Start Just pressing START + MODE button.
- Selectable Deflation Speed 2.5 mmHg / Sec. or 5.0 mmHg / Sec.



(with backlight)

Specifications

Model Name

UM-211 / UM-212BLE

Measurement method	Oscillometric measurement and Auscultatory measurement with stethoscope
Measurement range	Pressure:0 mmHg - 299 mmHg Pulse:40-200 beats / minute
Measurement accuracy	Pressure:±3 mmHg, Pulse:±5 %
Power supply	AC 100 V - 240 V (Rechargeable Battery)
Battery life	Approx. 300 measurements
Memory storage	Last 99 measurements
Operating conditions	+5 °C to 40 °C / 10 %RH to 85 %RH / 800 hPa to 1060 hPa
Transport / Storage conditions	-20 °C to +60 °C / 10 %RH to 95 %RH
Dimensions	Approx. 120 <w> x 200<h> x 140<d> mm</d></h></w>
Weight	Approx. 550 g (Unit without Bat tery)

Option


Adultcuff

AC Adapter AC Cable

REF:	Option Name
UM-LLRS4K1KEC	LL Cuff (41 cm - 50 cm)
UM-LARS4K1KEC	Large Cuff (31 cm - 45 cm)
UM-AURS4K1KEC	Adult Cuff (22 cm - 32 cm)
UM-SARS4K1KEC	Small Adult Cuff (16 cm - 24 cm)
UM-SSRS4K1KEC	SS Cuff (12 cm - 17 cm)
UM-211-20	Battery Pack
TB-268	AC Adapter
KO1886/7/8/9	AC Cable (A/C/BF/O Plug)
UM-ST002	Mobile Stand for UM-211
Standard accessories Option cuff (5 sizes)	

BatteryPack

External dimensions(mm/inches) with optional stand UM-ST002





A&D Company Limited.(JAPAN) URL:aandd.jp

A&D ENGINEERING, INC.(USA) URL:andonline.com

A&D Instruments Canada Inc.(CANADA) URL:autocontrol.com

A&D INSTRUMENTS LIMITED(United Kingdom) URL:andprecision.com

A&D AUSTRALASIA PTY LTD(Australia) URL:andaustralasia.com.au

A&D RUS CO., LTD. (Russia) URL:and-rus.ru

A&D Technology Trading(Shanghai)Co., Ltd(China) URL:aanddtech.cr

A&D INSTRUMENTS INDIA PRIVATE LIMITED(India) URL:aanddindia.in